## **PE Protection Film**



## **TECHNICAL DATA SHEET**

**PRODUCT: H70100** 

**PROPERTIES:** A green tinted 70 micron PE film with a coating of solvent acrylic adhesive. The product adheres well to both glass and aluminum and removes cleanly with no adhesive residue.

**FEATURES:** Excellent weatherability; stable adhesive strength; UV resistance up to 6 months; can be easily applied and removed leaving no adhesive residue.

**DIMENSIONS:** 1200mm X 100 or 200M Standard widths 1 x 1200mm or 2 x 600mm Special log cuts by order.



Properties	Unit Measure	Values and Characteristics
Environment condition temperature	Celsius degree	20±10%
Atmospheric pressure	mmHg	760±5%
Relative humidity	%	80±10%
Backing material		PE
Thickness of film	mm	0.067
Thickness of glue	mm	0.003
Type of Adhesive		Acrylic solvent
Total thickness	mm	0.07
Backing tensile strength	kgf/25mm	2.215
Adhesion	G/25mm	300±10%
Unwinding force	G/25mm	50±10%
Static shear 23c	Hours	>48
Elongation at break	%	>200
Outdoor Life/UV Resistance	Months	6 months



21A Shafton Street Huntingdale Vic 3166 Telephone:(03) 9544 1977 Facsimile:(03) 9544 7113 Web: www.budgetgroup.net